

# Spray extraction two-step process (indirect method)












# Spray extraction

## two-step process (indirect method)



### Description

<b>Definition / objective</b>	<b>Removing</b> heavy, stubborn, deep-seated soiling from floor coverings in two work steps using the spray extraction machine. Suitable for water-resistant, textile floor coverings, carpets, textiles or upholstery.
<b>Preparatory work</b>	Select suitable products to match the surface to be cleaned (type / square metres) and the type of soiling.
	Check whether the entire floor covering is water-resistant.
	Check, equip and ready the machine and all accessories in compliance with the instructions for use.
	 Fill the pressure sprayer with the cleaning product in accordance with the dosing instructions. Close the pressure sprayer and build up pressure (pumping). Fill the fresh water tank of the spray extraction machine with clear water.
	 Put up the warning sign.
	  Remove any loose dirt (dry vacuuming or brush vacuuming).
<b>Main task</b> <b>1. Work step (pre-spraying)</b>	 Use the pressure sprayer to evenly <b>spray</b> the textile floor covering with a sufficient amount of <b>cleaning product solution, working in slightly overlapping passes.</b>
	 Allow the cleaning product solution to take effect, but don't let it dry.
<b>Main task</b> <b>2. Work step (spray extraction / rinsing)</b>	 Spray extract the textile floor covering with water. Moving in slightly overlapping passes, pull the spray extraction nozzle slowly backwards, spray the pressurised water into the floor covering via the spray nozzles and immediately remove the dissolved dirt and the remaining cleaning solution using the suction nozzle. Repeat the process until the vacuumed rinsing water runs clear.
	Empty the waste water tank when it is full. Refill the fresh water tank when it is empty.
	As needed: Straighten the moist carpet pile using a carpet pile brush.
	 Perform a visual check.
	 Allow the textile floor covering to dry <b>completely.</b>
<b>Final steps</b>	Vent, empty and clean the pressure sprayer in accordance with the instructions for use.
	Vent, empty and clean the spray extraction machine in accordance with the instructions for use.
	Clean the spray nozzles and the suction nozzle.
	Check the power cable for visible damage, clean the cable and roll it up loosely towards the plug.
	Remove the warning sign once the floor covering is dry.
	Dispose of any waste.
	Clean the cleaning equipment and replace as needed.
<b>Comments</b>	<ul style="list-style-type: none"> <li>- Wear the personal protective equipment (PPE) required by company regulations, safety data sheets and / or instructions for use.</li> <li>- Always check in advance which product meets your requirements (see Wetrok Cleaning &amp; Care Instructions).</li> <li>- Wetrok AG accepts no liability for damage caused by improper use or incorrect product selection.</li> </ul>